Material Safety Data Sheet

Date: March 26,2013

Name of Product: KOPPER KARE, KOPPERSOL

Product Information: Topical Liquid

Product Code: 10L-KKARE

D.I.N.: 00603481 (Drug Identification Number)

Manufacturer/Supplier: Dominion Veterinary Laboratories Ltd.

1199 Sanford Street

Winnipeg, Manitoba R3E 3A1 Telephone: (204) 586-3484

Fax: (204) 943-9612

Product Identification

Product Use: Kopper Kare is used in the treatment of foot rot on cattle and sheep; thrush, hoof punctures and cracked hooves in horses; ringworm; wounds; after dehorning; as a pad toughener in dogs; and also for spongy hooves. It is a fungicide-antiseptic-astringent liquid.

Chemical Identity: Blend

CAS No. and Name:

Mineral Spirits: 8052-41-3

8% Copper Naphthenate: 1338-02-9

Formula and M. Wt.: Blend

Regulatory Section

WHMIS Classification:

8% Copper Naphthenate: Flammable Liquid, Class 3

Mineral Spirits: Flammable Liquid, Class 2

TDG Classification: Flammable Liquid, n.o.s. (Petroleum Distillates)

Class 3 UN 1993

Packing Group III

Hazardous Ingredients of Material

Hazardous Ingredients:

Mineral Spirits: Light Distillate, Trimethyl Benzene

8% Copper Naphthenate

Chemical Identity	CAS#/NA#/UN#	Conc. (w/w)	LD50
8% Copper Naphthenate	13380206 / 1306	70-90%	5050 mg/kg (oral rat)
Mineral Spirits	80454135	N/A	5000 mg/kg (oral rat)

Physical / Properties Data

Physical State: Partially slurried liquid.

Appearance and Odour: Dark green liquid; paint like odour.

Odour Threshold: 8% Copper Naphthenate: N/A **Boiling Pt. (Deg. C):** N/A

Mineral Spirits: N/A

Specific Gravity: 0.872 Freezing Pt. (Deg. C): N/A

Vapour Pressure: N/A pH: N/A

Evaporation Rate: N/A **Water Solubility:** Not soluble in water

Reactivity Data

Chemical Stability: N/A

Incompatible Substances: Strong oxidizing agent

Conditions of Reactivity: N/A

Hazardous Decomposition Products: N/A

Fire or Explosion Hazards

Conditions of Flammability: Flammable with source of ignition.

Means of Extinction:

Large Fires: Use an all purpose type AFFF foam according to foam manufacturer's recommended techniques. The foam supplier should be consulted for recommendation regarding foam types and delivery rates for specific applications.

Small Fires: Use carbon dioxide or dry chemical media.

Flash Point and Method of Determination: (Deg. C) 52 Deg. C (Pensky-Martens)

Upper Flammable Limit: N/A

Lower Flammable Limit: N/A

Auto-Ignition Temperature: N/A

Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide and Smoke

Light Distillate, Trimethyl Benzene

Explosion Data - Sensitivity to Mechanical Impact: Stable

Explosion Data - Sensitivity to Static Discharge: Material will accumulate static charge which may cause an incendiary electrical discharge.

Effects of Acute Exposure

Route of Entry:

Skin Contact: Minimal absorption.

Eye Absorption: Slightly irritating but should not injure eye tissue.

Inhalation: Prolong or repeated exposure to high vapor concentrations may cause headache,

nausea and/or dizziness.

Ingestion: High toxicity.

Effects of Chronic Exposure: Prolong or repeated exposure to high vapor concentration may cause headache, nausea and/or dizziness.

Toxicological and Health Data

Exposure Limits: N/A

Irritancy of Product: Prolong or frequent contact my irritate the skin and cause dermatitis.

Skin:

Eye: Slight irritating but should not injure eye tissue.

Sensitization to Material: N/A

Carcinogenicity: N/A

Reproductive Toxicity: N/A

Teratogenicity: N/A

Mutagenicity: N/A

Toxicological Synergistic Products: N/A

Preventive Measures

Personal Protective Equipment: Safety glasses, impermeable rubber gloves, synthetic apron, respirator or a half mask air purifying cartridge respirator.

Engineering Controls: Local mechanical exhaust ventilation capable of maintaining emissions at the point of use below the lowest pel.

Handling Procedures and Equipment: Avoid heat, sparks, and open flames.

Storage Requirements: Store in a cool, dry, well ventilated place away from incompatible materials, vent container frequently and more often in warm weather to relieve pressure. Protect material from direct electrical spark (ignition source).

Special Shipping Information: No special shipping requirements.

The information contained herein is, to the best of our knowledge, true and accurate. Any recommendations or suggestions are made without obligation on our part and the Company accepts no liability to any customers, their employees or any other person whatsoever for any loss, injury or damage whether direct or consequential, which may be caused by an error or emission from this sheet even if negligence or otherwise.

f:\user\lab\msds\kopper.doc